



 230V ac


Hz 50-60Hz

 CII

 1 CANAL/ 2 VÍAS


 IP44 PLUG


 IP65

 120°

 SMD 2835

 -20°C~+60 °C

 1m


 12x6mm

 60

 30.000h

 Max. 50m

 Rollo 50m

 340x340x110mm

 8,16kg (NW)

 8,64kg (GW)

 REG. TRIAC PRILUX

 INC.


Ñ/ EXTERIOR/TEXTURA LISA/TAPA FINAL INCLUIDA E/ OUTSIDE/SMOOTH TEXTURE/END COVER INCLUDED F/ À L'EXTERIEUR/TEXTURE LISSE/COUVER-CLE INCLUS P/ EXTERIOR/TEXTURA LISA/TAMPA FINAL INCLUIDA

Referencias/



Barcode	LED Icon	W%	W	K	φ	Beam Angle	Beam Spread
588171		9,5W	475W	3.858K	727,5lm/m	>81	
576031		9,5W	475W	2.855K	650,73lm/m	>82,9	
588959		5W	250W	-	-	-	
576048		5W	250W	-	-	-	
576055		5W	250W	-	-	-	
576062		5W	250W	-	-	-	


Dimensiones/



Accesorios/Accessories/Accessoires/Accessórios



CABLE ALIMENTACIÓN MAXIBRILLO



230Vac


W

Max. 480W



IP44 Plug
IP65 Conector

CONECTOR MACHO MAXIBRILLO




576093



Bl Blanco

TAPA FINAL MAXIBRILLO




576123



T Transparente

EMPALME ESTANCO MAXIBRILLO




576116



T Transparente

EMPALME SIMPLE MAXIBRILLO



576109



Bl Blanco